

3M 2000112



Details

- 11/16 in. (17.5 mm) gate opening steel carabiner
- Self-closing and locking gate for added safety
- Highly corrosion resistant plated hardware
- High strength steel construction
- User friendly compact and lightweight design

Our anchorage connectors are built from top quality materials guaranteeing high strength and durability to stand up to the toughest environments. Anchorage connectors are the unsung heroes of most fall protection systems, often overlooked but critical components because they securely attach your system to the anchorage. Your choice of anchor depends on the type of work being done. Anchorages are sold by what they connect to (general/all purpose, steel, concrete, roof or specialty), whether they are fixed or mobile, and whether they are permanent or portable. They all must provide a secure point of attachment for a complete personal fall arrest system, and must be capable of supporting a load of 5,000 lbs. (22kN) or of meeting OSHA's criteria of a 2-to-1 safety factor.

Specifications

| | |
|-------------------------|---|
| Attachment Type | Hook |
| Brand | Saflok™ |
| Carabiner/Hook Material | Zinc Plated Steel |
| Case Quantity | 1 |
| Color | Yellow Zinc |
| Dimensions | 4.33x2.66x0.75in |
| Install Type | Reusable |
| iSafe Equipped | No |
| Product Series | Saflok™ |
| Product Type | Carabiner |
| Recommended Industry | Construction, General Industrial, Mining, Oil & Gas, Transportation |
| Standards/Approvals | ANSI Z359.1, OSHA 1910.66, OSHA 1926.502 |
| Weight | 0.6 lb. |
| Weight (metric) | 0.3 kg |
| Weight Capacity | 310 lbs. (141 kg) ANSI / 420 lbs. (190 kg) OSHA |