

# 3M 2000114



## Details

- 2-3/16 in. (55.5mm) gate opening steel carabiner
- Self closing double action aoutolok gate for added safety
- Highly corrosion resistant plated hardware
- High strength steel construction
- User friendly compact and lightweight design

Our anchorage connectors are built from top quality materials guaranteeing high strength and durability to stand up to the toughest environments. Anchorage connectors are the unsung heroes of most fall protection systems, often overlooked but critical components because they securely attach your system to the anchorage. Your choice of anchor depends on the type of work being done. Anchorages are sold by what they connect to (general/all purpose, steel, concrete, roof or specialty), whether they are fixed or mobile, and whether they are permanent or portable. They all must provide a secure point of attachment for a complete personal fall arrest system, and must be capable of supporting a load of 5,000 lbs. (22kN) or of meeting OSHA's criteria of a 2-to-1 safety factor.

## Specifications

Attachment Type	Hook
Brand	Saflok™
Carabiner/Hook Material	Zinc Plated Steel
Case Quantity	1
Color	Gold, Yellow Zinc
CoWorker Controlled Ascent	No
CoWorker Controlled Descent	No
Dimensions	9.20x5.20x0.87in
Install Type	Reusable
iSafe Equipped	No
Product Series	Saflok™
Product Type	Carabiner
Recommended Industry	Construction, General Industrial, Mining, Oil & Gas, Transportation, Utilities, Wind Energy
Standards/Approvals	ANSI A10.32, ANSI Z359.1, OSHA 1910.66, OSHA 1926.502
User Controlled Ascent	No
User Controlled Descent	No
Weight	755 g
Weight Capacity	310 lbs. (141 kg) ANSI / 420 lbs. (190 kg) OSHA