

StanSolv AF-18

DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (inches) 13»
- Thickness (inches) .018 (18 mil)
- Wrist Straight cuff
- Colour/Color Green
- Interior finish Flocked
- Exterior finish Embossed texture
- Size / EAN 6 7 8 9 10 11
- Packaging 12 pairs/bag - 72 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



JKL

4101

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS
 0-4 0-5 0-4 0-4
 └─ Abrasion resistance
 └─ Blade cut resistance
 └─ Tear resistance
 └─ Puncture resistance



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374



RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS
 0-4 0-4 0-4 0-4 0-4 0-4
 └─ Burning behaviour
 └─ Contact heat resistance
 └─ Convective heat resistance
 └─ Radiant heat resistant
 └─ Resistance to small drops of molten metal
 └─ Resistance to large quantities of molten metal



SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS
 0-4 0-4 0 or 1
 └─ Convective cold resistance
 └─ Contact cold resistance
 └─ Water permeability

For more details: www.mapa-pro.com

MAPA[®]
 PROFESSIONAL
www.mapa-pro.com

DESCRIPTION AND GENERAL PROPERTIES

- Excellent dexterity, due to the suppleness of the glove
- Flock lining offers added comfort and absorbs perspiration during extended wear
- Unique Z-pattern grip provides an excellent grip, even on hard-to-grasp materials.

MAIN FIELDS OF USE

Automotive/mechanical industry

- Assembly of small oily parts
- Assembly of small, oil and grease free parts

Chemical industry

- Common handling Tasks
- Handling and transporting chemicals (solvents)

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Persons sensitized to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their original packaging protected from light, humidity and heat.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
 - in use with a solvent (alcohols, diluents, etc.) : rub over with a dry cloth
 - in use with acids or alkalies : thoroughly rinse the gloves in use with under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to any cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

Food contact US

FDA 21CFR 177.2600

LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0072/014/162/04/06/0029

- Issued by the notified body nr

0072

I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX