

FREE-SAT™

Safety Data Sheet

Revision date: 10/14/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name. : FREE-SAT
Product code : FS-NT1-77, FS-NT1-99, FS-NT1-712, SS-NT1-77, FS-NTP-711, FS-NTP-911,
FS-NTP-1711.85, FS-NT1-912CB, FS-NTP-911.35CB

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial cleaning wipes

1.3. Details of the supplier of the safety data sheet

High-Tech Conversions Inc
1699 King Street
Enfield, CT 06082

1.4. Emergency telephone number

T 860-265-2633 - F 860-265-2774

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)


Flam. Liq. 2 H225 - Highly flammable liquid and vapour
Acute Tox. 4 (Oral) H302 - Harmful if swallowed
Eye Irrit. 2A H319 - Causes serious eye irritation
STOT SE 3 H336 - May cause drowsiness or dizziness

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting/... equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash ... thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P312 - If swallowed: Call a poison center/doctor/... if you feel unwell
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a poison center/doctor/... if you feel unwell
P330 - Rinse mouth
P337+P313 - If eye irritation persists: Get medical advice/attention
P370+P378 - In case of fire: Use ... to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

FREE-SAT™

Safety Data Sheet

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Isopropyl alcohol	(CAS No.) 67-63-0	10 - 99	Flam. Liq. 2, H225
Deionized Water	(CAS No.) 7732-18-5	Balance	None

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
First-aid measures after skin contact	: Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists.
First-aid measures after eye contact	: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get medical attention.
First-aid measures after ingestion	: If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting unless directed to do so by medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May cause moderate irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water, foam, carbon dioxide, or dry chemical.
Unsuitable extinguishing media	: Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: None known.

5.3. Advice for firefighters

Protection during firefighting	: Firefighters should wear full protective gear.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment	: No special measures required.
Methods for cleaning up	: Collect spillage. Dispose of waste in accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with eyes, skin and clothing.
-------------------------------	---

FREE-SAT™

Safety Data Sheet

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls : General (mechanical) room ventilation is expected to be satisfactory for normal handling.
Hand protection : In case of repeated or prolonged contact wear gloves.
Eye protection : None required under normal product handling conditions.
Skin and body protection : Wear suitable working clothes.
Respiratory protection : If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid
Appearance : Pre-moistened wipes
Colour : Colorless
Odour : Alcohol-like.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : 37.8 °C
Self ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Specific gravity : 0.97
Solubility : No data available
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

FREE-SAT™

Safety Data Sheet

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Heat, flames, and other ignition sources.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rat	12800 mg/kg
LD50 dermal rabbit	12870 mg/kg
LC50 inhalation rat (mg/l)	72.6 mg/l (Exposure time: 4 h)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Isopropyl alcohol (67-63-0)	
IARC group	3

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified
Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
Symptoms/injuries after skin contact : May cause moderate irritation.
Symptoms/injuries after eye contact : Causes serious eye irritation.
Symptoms/injuries after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Isopropyl alcohol (67-63-0)	
LC50 fishes 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 other aquatic organisms 2	> 1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

FREE-SAT™

Safety Data Sheet

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

UN-No.(DOT) : 3175
 DOT NA no. UN3175

14.2. UN proper shipping name

DOT Proper Shipping Name : Solids containing flammable liquid, n.o.s. (Isopropanol)
 Department of Transportation (DOT) Hazard Classes : 4.1 - Class 4.1 - Flammable Solid 49 CFR 173.124
 Hazard labels (DOT) : 4.1 - Flammable solid



DOT Symbols : G - Identifies PSN requiring a technical name
 Packing group (DOT) : II - Medium Danger
 DOT Special Provisions (49 CFR 172.102) : 47 - Mixtures of solids that are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Except when the liquids are fully absorbed in solid material contained in sealed bags, each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed into a solid material are not subject to this subchapter provided there is no free liquid in the packet. IB6 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2). Additional Requirement: Composite IBCs 11HZ2 and 21HZ2 may not be used when the hazardous materials being transported may become liquid during transport. IP2 - When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle. T3 - 2.65 178.274(d)(2) Normal..... 178.275(d)(2)
 TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
 DOT Packaging Exceptions (49 CFR 173.xxx) : 151
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 212
 DOT Packaging Bulk (49 CFR 173.xxx) : 240

SECTION 15: Regulatory information

15.1. US Federal regulations

Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)

15.2. US State regulations

Isopropyl alcohol (67-63-0)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List	

FREE-SAT™

Safety Data Sheet

Isopropyl alcohol (67-63-0)

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases: see section 16:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.